

## Culvert and Driveway Policy Bullet Points

- All driveways need a permit. Permits are \$200 (cash/check) or \$200 plus a 2.5% administration fee, if using a debit/credit card when paying in person at the Road and Bridge Department location. You may also pay \$200 with debit/credit online at: <https://www.randallcounty.com/road/AccessInfo.html> .
- All permits are issued by the Road and Bridge Department. To receive a signed/approved copy of the permit or if you have any questions please call (806) 655-3861 or stop by the office at 301 W Highway 60, Canyon, Texas
- County personnel will assist in guidance on policy procedures
- Dip drives are allowed on ditches less than 15 inches deep
- All other drives shall have a culvert installed with a minimum of 24 inches inside diameter and made of concrete or corrugated tinhorn
- Must have a minimum of 8 inches of material on surface or manufacture recommendations
- Width of drive not to exceed 30 feet prior to approval from Randall County; with 6 to 1 sloped concrete ends are mandatory as of January 2018 (See Safety End Treatment standards document)
- Material may have to be removed from ditch to allow for driveway to be put in level
- Needs an all-weather surface such as, caliche, asphalt, or concrete, unless connecting to a dirt roadway
- A string line from edge of pavement to right-of-way line may be used to help set in culverts at the proper depth
- All non-permitted culverts/drives will be subject to removal

See Access Management Standards document for full details.